

Mirage is an inkjet Full-Body Italian Porcelain. Mirage has taken advantage of all the newest and latest inkjet technology to achieve the look of real stone including the natural veining and shading that occurs. The end result is a random yet controlled mixing of hues and surfaces within each stone color.



Glacier



Mountains



Waterfall



Mantle



River

Colors are intended as a guide only and may vary from actual tile. Please check tile samples before making final selections. See reverse side for additional product information.

PRODUCT INFORMATION

Sizes (Rectified) (R10 B)

MEQR--/1212	12 x 12
MEQR--/1224	12 x 24
MEQR--/2424	24 x 24

Colors

GROUP 1

MEQR03	Waterfall (med. grey)
MEQR04	River (dk. grey)

GROUP 2

MEQR01	Glacier (lt. grey)
MEQR02	Mountains (beige)
MEQR05	Mantle (charcoal)

Trim

The surface bullnose is made from field that is cut and ground.

MEQR--/SBN	3 x 24 Surface Bullnose
------------	-------------------------


Non-Stock Sizes (rectified)

For projects that meet minimum quantities.

MEQR--/812	8 x 12
MEQR--/824	8 x 24
MEQR--/1624	16 x 24
MEQR--/2448	24 x 48

Non-stock *Anti-slip* finish in 12 x 24 only - (R12 C per European Standards)

MEQR--A/1224	12 x 24
--------------	---------

Color: Waterfall (MEQR03)	
20% Pre-consumer Recycled Ceramic Content	
Color: River (MEAD04)	
Mantle (MEAD05)	
40% Pre-consumer Recycled Ceramic Content	
This product contributes towards satisfying MR credit 4.1 or 4.2 under LEED®.	

Usage

Quarziti 2.0 is suitable for floors, walls, counters, residential and commercial installations. It is important to blend tiles within each carton, and from different cartons during installation to insure a proper range of variation.

Technical Information

 Frost Resistance	 Water Absorption	 Slip Resistance	Coefficient of Friction	Dynamic & Static Coefficient of Friction
No Damage	.005%	R10 B	WET: ≥0.60 DRY: ≥0.60	≥0.42

The Coefficient of Friction is a general guide only. Testing may vary with different production runs and with different testing labs. As noted in the American with Disabilities Act (ADA) the coefficient of friction varies considerably due to facts not under the control of entities such as the manufacturers and distributors. These factors include, but are not limited to, contaminants, slope of terrain, drainage conditions, adjacent surfaces, etc. Suitability for any installation can only be determined by a site examination of all conditions that could affect the slip resistance of the tile being installed. Continual cleaning and maintenance must be performed once the tile has been installed. For more information see our current handout Americans with Disabilities Act and Slip Resistance of Tile.